


## HC49SM




Quartz Crystal Unit HC49SM, h = 4.5mm max.

- Standard Quartz Crystal SMD with 2 pads
- Metal Case
- on Tape & Reel
- Available in many standard and special frequencies
- RoHS conform; Lead-free product

### External Dimensions



### Soldering Conditions



## Specifications - Product No. A005529600BAFEPN43DB

|                               |                            |
|-------------------------------|----------------------------|
| Holder Type:                  | HC-49SM with 2 pads        |
| Frequency:                    | 5.529600 MHz               |
| Frequency Stability at 25°C:  | ±30 ppm                    |
| Temperature Stability:        | ±50ppm @ -40°C to +85°C    |
| Storage Temperature:          | -50°C to +105°C            |
| Drive Level:                  | 100µW (500µW max.)         |
| Load Capacitance (CL):        | 30 pF                      |
| Shunt Capacitance (C0):       | < 7pF                      |
| Crystal Cut & Vibration Mode: | AT- cut, fundamental       |
| Equivalent Series Resistance: | 150 Ohm max.               |
| Aging:                        | < ±3ppm max. / year (max.) |

### GERMANY:

COMTEC CRYSTALS GmbH · Sultenstrasse 12-14  
8 5 5 8 6 P o i n g / G E R M A N Y  
Phone +49 8121 778160 · Fax +49 8121 778177  
e-Mail [info@comtec-crystals.com](mailto:info@comtec-crystals.com)  
Internet: <http://www.comtec-crystals.com>  
Subject to change without prior notice.



Technical Data and Graphics are all under  
Copyright (c) of Comtec Crystals Group.

### FRANCE:

COMTEC CRYSTALS SARL · 23, rue du Faucon  
6 7 5 0 0 H a g u e n a u / F R A N C E  
Phone +33 388 732162 · Fax +33 388 730118  
e-Mail [sales@comtec-crystals.com](mailto:sales@comtec-crystals.com)  
Internet: <http://www.comtec-crystals.com>  
Sous réserve de modifications.