





MEMS Oscillator MEP5032T 3.3V/2.8/2.5V/1.8V
Programmable from 1 to 150MHz

- SMD Plastic Packaging (5.0 x 3.2 x 0.85) mm
- Excellent Shock and Vibration Resistance
- CMOS/TTL Square Wave
- on Tape & Reel (Tape 12mm)
- RoHS conform; Lead-free product
- Available in many standard and special frequencies



Specifications

| | |
|----------------------------------|---|
| Holder Type: | MEP5032T 3.3V/2.8/2.5V/1.8V |
| Frequency: | 0.000000 kHz |
| Frequency Stability at 25°C: | ± 25 ppm |
| Operating Temperature Range: | -40°C to +85°C |
| Storage Temperature: | -55°C to +150°C |
| Power Supply Voltage (Vdd): | -0.3Vmin. to +4.0Vmax. |
| Maximum Supply Current, no load: | |
| Standby Current: | I _{dd} , T = 25°C, 15µA |
| Output Load: | 15 pF CMOS / 10LS TTL gates max. |
| Output Symmetry (Duty Cycle): | 45/55% |
| Output Voltage (VOH) (VOL): | 90% of Vdd min. / 10% of Vdd max. |
| Rise/Fall Time (10% to 90% Vdd): | 10 ns max. < 5 ns typical |
| Start Up Time: | 10 ms max. < 5 ms typical |
| Tri-state Function Pin 1: | Pin 1 = H or open.... Output active at pin 3 Pin 1 = L.... high impedance at pin 3 |
| Aging: | < ± 5ppm max. / year (max.) |
| Reflow Condition: | 260°C max for 40 sec. |

GERMANY:

COMTEC CRYSTALS GmbH · Sultenstrasse 12-14
8 5 5 8 6 P o i n g / G E R M A N Y
Phone +49 8121 778160 · Fax +49 8121 778177
e-Mail info@comtec-crystals.com
Internet: <http://www.comtec-crystals.com>
Subject to change without prior notice.



Technical Data and Graphics are all under
Copyright (c) of Comtec Crystals Group.

FRANCE:

COMTEC CRYSTALS SARL · 23, rue du Faucon
6 7 5 0 0 H a g u e n a u / F R A N C E
Phone +33 388 732162 · Fax +33 388 730118
e-Mail sales@comtec-crystals.com
Internet: <http://www.comtec-crystals.com>
Sous réserve de modifications.