



VCXO-Oscillator SMD VCXO5032T1.8-4pad 1.8V Voltage Controlled Crystal Oscillator

- Output Wave Form CMOS
- SMD in ceramic case (5.0 x 3.2 x 1.2) mm
- RoHS conform; Lead-free product
- Vibration: MIL-STD-202F method 204, 35G, 50 to 2000 Hz
- Shock: MIL-STD-202F method 213B, test cond. E, 1000G 1/2 sine wave
- Available in many standard and special frequencies



Specifications - Product No. G025000000KI SUPC43AB

Holder Type:	VCXO5032T1.8-4pad 1.8V (Voltage code is "1.8")
Frequency:	25.000000 MHz
Initial Freq. Accuracy (at 25 °C):	To tune to the nominal frequency with Vc = 1.25V ± 0.2V
Freq. Stability o. Operating Temp. Range:	± 25.0 ppm
Operating Temperature Range:	± 25.0 ppm over -40°C to +85°C (inclusive of 25°C tolerance, ± 10% input voltage variation, load change, aging, shock and vibration)
Frequency Deviation:	± 100ppm
Power Supply Voltage (Vdd):	+1.8V DC ± 10%
Maximum Supply Current:	12.0 mA
Output Load CL:	CMOS 15 pF
Output "1" Level (VOH):	2.25V (min.) CMOS
Output "0" Level (VOL):	0.25V (max.) CMOS
Output Symmetry (Duty Cycle):	45/55%
Voltage Control:	0.9V DC Center / 0.00V to 1.8V Range
Linearity:	6% typical; 10% max.
Rise/Fall Time:	6ns (max.) 4ns (typ.) Measured between 0.4V and 2.4V
Integrated Phase Jitter:	1 ps max. (12 kHz to 20 MHz)
Phase Noise (27MHz at 3.3V):	-75dBc/Hz at 10Hz offset -145dBc/Hz at 10kHz offset -104dBc/Hz at 100Hz offset -152dBc/Hz at 100kHz offset -132dBc/Hz at 1kHz offset -150dBc/Hz at 1MHz offset
Start Up Time:	10 ms (max.), 5ms (typ.)
Aging:	± 3 ppm per year (max.)
Reflow Condition:	10 sec. max. at 260°C

GERMANY:

COMTEC CRYSTALS GmbH · Sultenstrasse 12-14
8 5 5 8 6 P o i n g / G E R M A N Y
Phone +49 8121 778160 · Fax +49 8121 778177
e-Mail info@comtec-crystals.com
Internet: <http://www.comtec-crystals.com>
Subject to change without prior notice.



Technical Data and Graphics are all under
Copyright (c) of Comtec Crystals Group.

FRANCE:

COMTEC CRYSTALS SARL · 23, rue du Faucon
6 7 5 0 0 H a g u e n a u / F R A N C E
Phone +33 388 732162 · Fax +33 388 730118
e-Mail sales@comtec-crystals.com
Internet: <http://www.comtec-crystals.com>
Sous réserve de modifications.