






CM309S





Quartz Crystal Unit CM309S

- Standard Quartz Crystal SMD with 4 pads
- Plastic Package
- on Tape & Reel
- RoHS conform; Lead-free product
- Available in many standard and special frequencies


External Dimensions



Recommended soldering pattern



Soldering Conditions



Specifications - Product No. A005000000DFEPN43BC

Holder Type:	CM309S with 4 pads
Frequency:	5.000000 MHz
Frequency Stability at 25°C:	± 50 ppm
Temperature Stability:	± 100 ppm @ -40°C to +85°C
Storage Temperature:	-55°C to +125°C
Drive Level:	100µW max.
Load Capacitance (CL):	30 pF
Shunt Capacitance (CO):	< 7pF
Crystal Cut & Vibration Mode:	AT- cut, fundamental
Equivalent Series Resistance:	150 Ohm max.
Aging:	< ± 5ppm max. / year (max.)

GERMANY:

COMTEC CRYSTALS GmbH · Sultenstrasse 12-14
 8 5 5 8 6 P o i n g / G E R M A N Y
 Phone +49 8121 778160 · Fax +49 8121 778177
 e-Mail info@comtec-crystals.com
 Internet: <http://www.comtec-crystals.com>
 Subject to change without prior notice.



Technical Data and Graphics are all under
 Copyright (c) of Comtec Crystals Group.

FRANCE:

COMTEC CRYSTALS SARL · 23, rue du Faucon
 6 7 5 0 0 H a g u e n a u / F R A N C E
 Phone +33 388 732162 · Fax +33 388 730118
 e-Mail sales@comtec-crystals.com
 Internet: <http://www.comtec-crystals.com>
 Sous réserve de modifications.