



Programmable Crystal Clock Oscillator
CXP7050TM3.3, 3.3V LVCMOS

- SMD in ceramic case (7.0 x 5.0 x 1.7) mm
- Tri-State Enable / Disable
- LVCMOS Square Wave
- on Tape & Reel (Tape 16mm) or on trays
- RoHS conform; Lead-free product
- Vibration: MIL-STD-202F method 204, 35G, 50 to 2000 Hz
- Shock: MIL-STD-202F method 213B, test cond. E, 1000GG 1/2 sine wave
- Available in many standard and special frequencies



Specifications - Product No. G029500000KSSUPN43AB

| | |
|------------------------------------|---|
| Holder Type: | Programmable Crystal Clock Oscillator CXP7050TM3.3 Tri-State 3.3V (Voltage code is " 3.3 ") |
| Frequency: | 29.500000 MHz |
| Frequency Stability at 25°C: | ± 25.0 ppm at 25°C |
| Operating Temperature Range: | ± 25.0 ppm over -40°C to +85°C (inclusive of 25°C tolerance, ± 10% input voltage variation, load change, aging, shock and vibration) |
| Storage Temperature: | -55°C to +150°C |
| Power Supply Voltage (Vdd): | + 3.3V D.C. ± 10% |
| Maximum Supply Current: | 20.0 mA |
| Max. Supply Current 25/200MHz: | 3.3V/4.0/20mA (15pF) |
| PLL Off: 25MHz Supply Current: | 3.3V 4.0mA (15pF) |
| PLL On 200MHz Supply Current: | 3.3V 20.0mA (15pF) |
| Rise/Fall Time: | 3.0ns typ. (25MHz, PLL off) 1.5ns typ. (200MHz, PLL off) |
| Output Load: | 15 pF LVCMOS |
| Start Up Time: | 5ms max. |
| Output Symmetry (Duty Cycle): | 50% ± 5% (measured at 50% Vdd) |
| Period Jitter, peak to peak: | 70ps typical |
| Low Phase Noise (typical): | -114dBc/Hz at 1KHz offset (133MHz) |
| Tri-state Function Pin 1 (option): | Pin 1 = H or open.... Output active at pin 3 Pin 1 = L.... high impedance at pin 3 |
| Output Disable/Enable Time: | 150 ns |
| Aging: | < ± 5ppm max. / year (max.) |
| Reflow Condition: | 260°C max. for 10 sec. |

GERMANY:

COMTEC CRYSTALS GmbH · Sultenstrasse 12-14
8 5 5 8 6 P o i n g / G E R M A N Y
Phone +49 8121 778160 · Fax +49 8121 778177
e-Mail info@comtec-crystals.com
Internet: <http://www.comtec-crystals.com>
Subject to change without prior notice.



Technical Data and Graphics are all under
Copyright (c) of Comtec Crystals Group.

FRANCE:

COMTEC CRYSTALS SARL · 23, rue du Faucon
6 7 5 0 0 H a g u e n a u / F R A N C E
Phone +33 388 732162 · Fax +33 388 730118
e-Mail sales@comtec-crystals.com
Internet: <http://www.comtec-crystals.com>
Sous réserve de modifications.